

STRATA CIX100



Strata CIX100 with DP5130F-SDL

Practical, scalable and easy-to-use. Between 8 and 72 extensions and up to 56 exchange lines.

Key benefits:

- » Modular design provides a flexible and cost-effective solution that allows you to add additional features and functionality as your business requires.
- » Designed for continuous technical enhancement so you will always have access to the latest technology, supporting your business to maintain its competitive advantage.
- » Unrivalled investment protection; easily upgrade to the Strata CIX200 or CIX670 with handsets, applications and system hardware being compatible across the Strata CIX range.
- » Flexible configurations allow you to implement IP telephony when it's right for your business easily and cost effectively.
- » Peer-to-peer technology in pure IP configuration ensures efficient use of bandwidth for remote users and branch office locations.
- » Common, extensive feature-set regardless of configuration, made available to all employees including those in branch offices, or working remotely.
- » Reduced cost of ownership through SIP trunking, available directly from the IP card to eliminate the need for an external gateway.
- » Full range of applications available to extend your solution, including built-in Uniform Call Distribution (UCD) and traffic reporting, messaging solutions, Automatic Call Distribution (ACD), call routing and recording, Interactive Voice Response (IVR), Computer Telephony Integration (CTI) and networking.

Strata CIX100 is a sophisticated, feature-rich communication system designed for organisations that require a practical, scalable and easy-to-use communication platform.

A compact and intelligent system, Strata CIX100 is highly flexible and provides you with a communication solution that will meet your needs today, whilst allowing your business to grow as required in the future.

Strata CIX100 can be configured as a pure or hybrid IP solution, or for traditional digital end-points. Whilst providing maximum flexibility, the Strata CIX100 also provides the whole range of features and extended functionality offered by the entire Strata CIX range.

Strata CIX100 Specification

Dimensions

Base Cabinet	Expansion Cabinet
Height = 370mm	Height = 370mm
Width = 303mm	Width = 230mm
Depth = 259mm	Depth = 259mm
Weight = 8.8kg (fully equipped)	Weight = 6.9kg (fully equipped)

Cabinet and Slot Capacities

Cabinets	1 or 2
Universal Slots	4 in base cabinet and 4 in expansion.
Port Capacity (lines and stations)	112

Station/Peripherals System Capabilities

Trunk Lines	56
IP Telephones	72
Digital Telephones	72
Analogue Standard Stations	64
Calls Existing at the Same Time	56
20-button Add-on Modules	61
60-button Direct Station Select	3
Attendant Consoles	2
Door Phones	6
Door Phone Control Boxes	2
Door Locks	4
Music on Hold Interfaces	15
Tenants	8
Multi-system Networking Nodes	128
System Call Forward Patterns	4
Call Park Orbits (general)	14
Call Park Orbits (individual)	56
Conferencing	8
Conference Party Types	6 lines 8 stations
DDI Numbers	450
Hunt Groups	90
Hunt Group Size	72
Hunt Group Stations	360
System Speed Dials	800
Verified Account Codes	135

System Administration

eManager	Browser-based administration with configuration wizards and multiple, configurable access levels.
My Phone Manager	Personal administration for individual users.

Technical Specifications

Power Supply (PSU)	One per cabinet.
Power Backup	Two or four 12v external batteries with ABCS charger can provide power backup operation for 12-50 hours depending on configuration.
Chassis Installation	Wall-mounted (preferable) or table top.
Operating Temperature	0 ~ 40°C
Operating Humidity	20 ~ 80% relative humidity without condensation.
Storage Temperature	-20 ~ 60°C